

PROTECTOR DECORATIVE AND ANTI-DUST TREATMENT BASED ON CHLORINATED RUBBERS

Edition: 4 06/2010

Technical department

Description:

Single-component product based on pure chlorinated rubber combined with mineral pigments with a very good light stability, conceived as a protective treatment, decorative and dustproof on concrete floors.

Uses:

As finishing on asbestos cement sheets and concrete floors both indoors and outdoors, with waterproof properties, very good adhesion to building holders, resistant to alkalinity, for moderate traffic areas.

Features & benefits:

* VERY LONG DURATION * GOOD WEATHER RESISTANCE
* VERY GOOD ATTRITION RESISTANCE * ANTI-DUST *
EASY TO APPLY *

Technical features:

Colour/s	White, green, tile red, grey, black and translucent.
Density	1,47 Kg./Lt. +- 0,07
Dry for repainting	12 hours at 20°
Dry upon touching	3 hrs a 20°C
Temperature of work	From 8 to 25°C
Viscosity	8.000 ± 4.000 mPa.s

Surface preparation:

Well set, dry, clean and free of greases, oils, incompatible paints, dust and loose particles.

Clean up:

With our solvent DISOLUAIS

Coverage:

3 sqm per litre.

Application

-Homogenize properly the package content.

-Apply on the cleaned support, a layer of IMPRIMAIS primer, IMPRIDUR or TAIS diluted at 50% with DISOLUAIS (for porous supports)

-Once the primer is dry TAIS must be applicate with all the layers that it needs by brush, roller or pistol (diluted with DISOLUAIS).

Packaging:

Available in packs of:

Storage:

1 year, in their original packagings, properly closed, without exposing to extreme temperatures and protected from weather conditions.

Health and safety advice:

Consult the safety information on the label on each package, and for more information refer to the product Material Safety Data Sheet.